

semi





DATE 17 NOV 2006

NOTES:

- 2. 3.
- DITES: DIMENSIONS AND TOLERANCING PER ASME Y14.5M, 1994. DIMENSIONS IN MILLIMETERS. DIMENSION & APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 MM FROM TERMINAL COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS. 4.

	MILLIMETERS		
DIM	MIN	MAX	
Α	0.80	1.00	
A1	0.00	0.05	
A3	0.20 REF		
b	0.18	0.30	
D	6.00 BSC		
D2	3.98	4.28	
E	5.00 BSC		
E2	2.98	3.28	
е	0.50 BSC		
K	0.20		
L	0.45	0.65	

GENERIC **MARKING DIAGRAM***

1	XXXXXXXXX XXXXXXXX AWI YYWW
	AWETTWW

XXXXX = Specific Device Code А

- = Assembly Location
- WL = Wafer Lot
- YΥ = Year
- WW = Work Week
 - = Pb-Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb–Free indicator, "G" or microdot " •", may or may not be present.

DOCUMENT NUMBER:	98AON11920D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	18 PIN DFN, 6X5 MM. 0.5 MM PITCH		PAGE 1 OF 1
-			

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.